

CTC005-910

Robot kolaboratif · CTC

Tanggal pemeriksaan katalog: 2026-10-08



Jumlah sumbu	6
Jangkauan	912 mm
Beban nominal	5 kg
Pengulangan posisi	≤ ±0.05 mm

Parameter lainnya

Berat robot	24 kg
Konsumsi daya	0.6 kW
Tingkat perlindungan	IP54

Disusun dari halaman produk produsen, dengan gambar model dan parameter lengkap. Pengelompokan tabel sumber dipertahankan; ejaan dan spasi label dirapikan. Ini kompilasi situs ini, bukan lembar spesifikasi yang diterbitkan produsen.

Tabel parameter lengkap

Collaborative arm parameters		
Function		Polishing, material handling, 3C products
Maximum effective working radius (Reach)		912 mm
Rated payload		5 kg
Repeat positioning accuracy		≤ ±0.05 mm
Body weight		24 kg
Power consumption		0.6 Kw
Operating environment temperature		0~60 °C
Operating environment humidity		0—90% (Non-condensing)
Mounting method		Any angle
Protection class		IP54
Degrees of freedom		6
Joint Motion Parameters		
Axis No.	Motion Range (Zero at Vertical Up)	Rated Speed
J1	±180°	3000 rpm
J2	±90°	3000 rpm
J3	±160°	3000 rpm
J4	±100°	3000 rpm
J5	±180°	3000 rpm
J6	±360°	3000 rpm