

CTC012-1280

Robot kolaboratif · CTC

Tarikh semakan katalog: 2026-10-08



Bilangan paksi	6
Jangkauan	1283 mm
Muatan berkadar	12 kg
Kebolehulangan kedudukan	≤ ±0.1 mm

Parameter tambahan

Berat robot	36 kg
Penggunaan kuasa	2.5 kW
Tahap perlindungan	IP54

Disusun daripada halaman produk pengeluar, dengan gambar model dan parameter lengkap. Pengelompokan jadual sumber dikekalkan; ejaan dan jarak label diperkemas. Ini kompilasi laman ini, bukan helaian spesifikasi yang diterbitkan pengeluar.

Jadual parameter lengkap

Collaborative arm parameters		
Function		Polishing, material handling, 3C products
Maximum effective working radius (Reach)		1283 mm
Rated payload		12 kg
Repeat positioning accuracy		≤ ±0.1 mm
Body weight		36 kg
Power consumption		2.5 Kw
Operating environment temperature		0~60 °C
Operating environment humidity		0–90% (Non-condensing)
Mounting method		Any angle
Protection class		IP54
Degrees of freedom		6
Joint Motion Parameters		
Axis No.	Motion Range (Zero at Vertical Up)	Rated Speed
J1	±180°	2000 rpm
J2	±90°	2000 rpm
J3	+250°/-70°	3000 rpm
J4	±100°	3000 rpm
J5	±180°	3000 rpm
J6	±360°	3000 rpm