

CTR008-900

Robot industri · CTR

Tarikh semakan katalog: 2026-10-08



Bilangan paksi	6
Jangkauan	915 mm
Muatan	8 kg
Kebolehulangan kedudukan	±0.03 mm

Parameter tambahan

Berat robot	60 kg
Penggunaan kuasa	2.2 kW
Tahap perlindungan	IP54

Disusun daripada halaman produk pengeluar, dengan gambar model dan parameter lengkap. Pengelompokan jadual sumber dikekalkan; ejaan dan jarak label diperkemas. Ini kompilasi laman ini, bukan helaian spesifikasi yang diterbitkan pengeluar.

Jadual parameter lengkap

Robot model	CTR008-900	
Function	Polishing, material handling, 3C products	
Total axes	6	
Payload	8kg	
Position repeat accuracy	±0.03mm	
Max speed	1st axis(底部旋转)	337.5°/sec
	2nd axis(大臂)	270°/sec
	3rd axis(小臂)	375°/sec
	4th axis(手腕旋转)	300°/sec
	5th axis(手腕摆动)	375°/sec
	6th axis(手腕旋回)	468°/sec
Max operating area	1st axis(底部旋转)	±170°
	2nd axis(大臂)	+100°/-135°
	3rd axis(小臂)	+110°/-155°
	4th axis(手腕旋转)	±170°
	5th axis(手腕摆动)	±120°
	6th axis(手腕旋回)	±360°
Working temperature	0~45°C	
Installation parameters	Floor mounted	
Robot weight	60Kg	
Power consumption	2.2kw	
Maximum reach	915mm	
Protection rating	IP54	