

CTR012-1450

Robot industri · CTR

Tanggal pemeriksaan katalog: 2026-10-08



Jumlah sumbu	6
Jangkauan	1450 mm
Beban	12 kg
Pengulangan posisi	±0.05 mm

Parameter lainnya

Berat robot	190 kg
Konsumsi daya	4.7 kW
Tingkat perlindungan	IP44

Disusun dari halaman produk produsen, dengan gambar model dan parameter lengkap. Pengelompokan tabel sumber dipertahankan; ejaan dan spasi label dirapikan. Ini kompilasi situs ini, bukan lembar spesifikasi yang diterbitkan produsen.

Tabel parameter lengkap

Robot model		CTR012-1450
Function		Polishing, material handling, 3C products
Total axes		6
Payload		12kg
Position repeat accuracy		±0.05mm
Max speed	1st axis(底部旋转)	220°/sec
	2nd axis(大臂)	220°/sec
	3rd axis(小臂)	220°/sec
	4th axis(手腕旋转)	375°/sec
	5th axis(手腕摆动)	375°/sec
	6th axis(手腕旋回)	450°/sec
Max operating area	1st axis(底部旋转)	±170°
	2nd axis(大臂)	+70°/-155°
	3rd axis(小臂)	+142°/-155°
	4th axis(手腕旋转)	±170°
	5th axis(手腕摆动)	±120°
	6th axis(手腕旋回)	±360°
Installation parameters		Floor mounted
Robot weight		190Kg
Power consumption		4.7kw
Maximum reach		1450mm
Installation environment	Temperature	0~+45°C
	Vibration	4.9M/S² below
	Protection rating	IP44