

CTR012-1450

Robot industri · CTR

Tarikh semakan katalog: 2026-10-08



Bilangan paksi	6
Jangkauan	1450 mm
Muatan	12 kg
Kebolehulangan kedudukan	±0.05 mm

Parameter tambahan

Berat robot	190 kg
Penggunaan kuasa	4.7 kW
Tahap perlindungan	IP44

Disusun daripada halaman produk pengeluar, dengan gambar model dan parameter lengkap. Pengelompokan jadual sumber dikekalkan; ejaan dan jarak label diperkemas. Ini kompilasi laman ini, bukan helaian spesifikasi yang diterbitkan pengeluar.

Jadual parameter lengkap

Robot model		CTR012-1450
Function		Polishing, material handling, 3C products
Total axes		6
Payload		12kg
Position repeat accuracy		±0.05mm
Max speed	1st axis(底部旋转)	220°/sec
	2nd axis(大臂)	220°/sec
	3rd axis(小臂)	220°/sec
	4th axis(手腕旋转)	375°/sec
	5th axis(手腕摆动)	375°/sec
	6th axis(手腕旋回)	450°/sec
Max operating area	1st axis(底部旋转)	±170°
	2nd axis(大臂)	+70°/-155°
	3rd axis(小臂)	+142°/-155°
	4th axis(手腕旋转)	±170°
	5th axis(手腕摆动)	±120°
	6th axis(手腕旋回)	±360°
Installation parameters		Floor mounted
Robot weight		190Kg
Power consumption		4.7kw
Maximum reach		1450mm
Installation environment	Temperature	0~+45°C
	Vibration	4.9M/S² below
	Protection rating	IP44