

CTS006-600

Robot SCARA · CTS

Tarikh semakan katalog: 2026-10-08



Bilangan paksi	4
Jangkauan	600 mm
Muatan berkadar	3 kg
Muatan maksimum	6 kg
Kebolehulangan kedudukan · XY	±0.02 mm

Parameter tambahan

Kebolehulangan kedudukan · Z	±0.01 mm
Kebolehulangan kedudukan · putaran	±0.01°
Lejang paksi Z	220 mm
Berat robot	17 kg
Penggunaan kuasa	0.8 kW

Disusun daripada halaman produk pengeluar, dengan gambar model dan parameter lengkap. Pengelompokan jadual sumber dikekalkan; ejaan dan jarak label diperkemas. Ini kompilasi laman ini, bukan helaian spesifikasi yang diterbitkan pengeluar.

Jadual parameter lengkap

Robot model	CTS006-600	
Function	Material handling, 3C products	
Total axes	4	
Maximum reach	600mm	
Payload	Rated load	3kg
	Maximum load	6kg
Permissible inertial torque of rotating axis	Rated torque	0.01kg.m ²
	Maximum torque	0.12kg.m ²
Position repeat accuracy	1st axis+2nd axis	±0.02mm
	3 Elevating axis	±0.01mm
	4 Rotation axis	±0.01°
Max speed	1st axis	450°/sec
	2nd axis	720°/sec
	3 Elevating axis	1000mm/sec
	4 Rotation axis	1800°/sec
Max operating area	1st axis	±132°
	2nd axis	±142°
	3 Elevating axis	220mm
	4 Rotation axis	±360°
Installation parameters	Floor mounted	
Robot weight	17Kg	
Power consumption	0.8kw	
Installation environment	Temperature	0~+45°C
	Humidity	20~80%R(No condensation)
	Vibration	4.9M/S ² below