

CTS010-800

Robot SCARA · CTS

Tarikh semakan katalog: 2026-10-08



Bilangan paksi	4
Jangkauan	800 mm
Muatan berkadar	5 kg
Muatan maksimum	10 kg
Kebolehulangan kedudukan · XY	±0.02 mm

Parameter tambahan

Kebolehulangan kedudukan · Z	±0.01 mm
Kebolehulangan kedudukan · putaran	±0.01°
Lejang paksi Z	200 mm
Berat robot	28 kg
Penggunaan kuasa	1.55 kW

Disusun daripada halaman produk pengeluar, dengan gambar model dan parameter lengkap. Pengelompokan jadual sumber dikekalkan; ejaan dan jarak label diperkemas. Ini kompilasi laman ini, bukan helaian spesifikasi yang diterbitkan pengeluar.

Jadual parameter lengkap

Robot model	CTS010-800	
Function	Material handling, 3C products	
Total axes	4	
Maximum reach	800mm	
Payload	Rated load	5kg
	Maximum load	10kg
Position repeat accuracy	1st axis+2nd axis	±0.02mm
	3 Elevating axis	±0.01mm
	4 Rotation axis	±0.01°
Max speed	1st axis	300°/sec
	2nd axis	375°/sec
	3 Elevating axis	1041mm/sec
	4 Rotation axis	1500°/sec
Max operating area	1st axis	±130°
	2nd axis	±145°
	3 Elevating axis	200mm
	4 Rotation axis	±360°
Installation parameters	Floor mounted	
Robot weight	28Kg	
Power consumption	1.55kw	
Installation environment	Temperature	0~+45°C
	Humidity	20~80%R(No condensation)
	Vibration	4.9M/S² below